

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

NEVASTANE XS 80

SDS #: 081734

previous revision date

: 2022/09/20

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name	: NEVASTANE XS 80
UFI	: C7C9-67VJ-H008-8FU2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses			
Extreme pressure			
Grease for incidental food contact			
Lubricating grease			
Use of lubricants and greases in open systems - Professional			
Formulation additives, lubricants and greases - Industrial			
General use of lubricants and greases in vehicles or machinery - Industrial			
General use of lubricants and greases in vehicles or machinery - Professional			
Use of lubricants and greases in open systems - Industrial			

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants 562 Avenue du Parc de L'ile 92029 Nanterre Cedex FRANCE Tél: +33 (0)1 41 35 40 00 Fax: +33 (0)1 41 35 84 71 rm.msds-lubs@totalenergies.com

TotalEnergies Marketing Deutschland GmbH Jean-Monnet-Straße 2 10557 BERLIN DEUTSCHLAND Tel: +49 (0)30 2027 60

msds@totalenergies.com

Contact

HSE : + 49 (0) 30/ 2027-9429

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number	: Giftnotruf Berlin, Tel.+49 (0)30 19240 (24 h erreichbar, Beratung in Deutsch und Englisch
<u>Supplier</u> Telephone number	: TOTAL Emergency number: +49 89 220 61012



SDS #: 081734

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Eye Irrit. 2, H319

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended. See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Hazard pictograms



Signal word	: Warning
Hazard statements	: H319 - Causes serious eye irritation.
Precautionary statements	
Prevention	: P280 - Wear eye or face protection.
Response	 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337 + P313 - If eye irritation persists: Get medical advice or attention.
Storage	: Not applicable.
Disposal	: Not applicable.
Supplemental label elements	: Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %. This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do : None known. not result in classification

Version : 3

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture



SDS # : 081734

Product/substance	Identifiers	% (w/w)	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	REACH #: 01-2119560592-37 EC: 932-231-6 CAS: 1335202-81-7	<3	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412	-	[1]
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	REACH #: 01-2119491299-23 EC: 270-128-1 CAS: 68411-46-1	≤1	Repr. 2, H361f	-	[1]
			See Section 16 for the full text of the H statements declared above.		

Additional information

: The product is made from synthetic base oils

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Туре

Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid r	neasures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed <u>Over-exposure signs/symptoms</u>



SDS # :

081734

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness			
Inhalation	: No specific data.			
Skin contact	: No specific data.			
Ingestion	: No specific data.			
4.3 Indication of any immedi	ate medical attention and special treatment needed			
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled. 			
Specific treatments	: No specific treatment.			
SECTION 5: Firefigh	ting measures			
5.1 Extinguishing media				
Suitable extinguishing media	: Use dry chemical, CO ₂ , water spray (fog) or foam.			
Unsuitable extinguishing media	: Do not use water jet.			
5.2 Special hazards arising f	rom the substance or mixture			
Hazards from the substance or mixture	: No specific fire or explosion hazard.			
Hazardous combustion products	: carbon monoxide carbon dioxide nitrogen oxides sulfur oxides Hydrogen sulfide Mercaptans			
5.3 Advice for firefighters				
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.			
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.			

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".



6.2 Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and materials for	r containment and cleaning up
Small spill	: Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.
Large spill	: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s) Recommendations : See exposure scenarios Industrial sector specific : Not available. solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Reportable hazardous constituent(s) contained in UVCB and/or multi-constituent substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

No exposure limit value known.

Biological Limit Values (BLV)

No exposure indices known.



Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Advisory OEL

: No known significant effects or critical hazards.

DNELs/DMELs

Product/substance	Туре	Exposure	Value	Population	Effects
enzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	DNEL	Long term Dermal	1.7 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	85 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	89 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	1.7 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	85 mg/kg bw/day	General population	Systemic
	DNEL	Short term Oral	89 mg/kg bw/day	General population	Systemic
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	DNEL	Long term Oral	0.04 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.04 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.08 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	0.14 mg/m ³	population	Systemic
	DNEL	Long term Inhalation	0.6 mg/m ³	Workers	Systemic

PNECs

	1		
Product/ingredient name	Compartment Detail	Name	Method Detail
enzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	Fresh water	23 µg/l	-
	Marine water	2.3 µg/l	-
	Sewage Treatment Plant	3 mg/l	-
	Fresh water sediment	174 µg/kg dwt	-
	Marine water sediment	17.4 µg/kg dwt	-
	Soil	620 µg/kg dwt	-
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	Fresh water	33.8 µg/l	-
	Marine water	3.38 µg/l	-
	Fresh water sediment	446 µg/kg dwt	-
	Marine water sediment	44.6 µg/kg dwt	-
	Soil	1.76 mg/kg dwt	-

8.2 Exposure controls

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Revision:2023/08/11	Version : 3	Germany	ENGLISH	6/35
---------------------	-------------	---------	---------	------



Individual protection measures

individual protection measu	res
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: 🖻 🎜 fety glasses with side-shields, EN 166.
Skin protection	
Hand protection	 Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. nitrile rubber Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency
Body protection	: Wear work clothing with long sleeves. Non-skid safety shoes or boots
Respiratory protection	: Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of inadequate ventilation wear respiratory protection: Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties

<u>Appearance</u>		
Physical state	: Solid. [grease]	
Color	: Brown.Clear.	
Odor	: Characteristic.	
рН	: Not applicable.	Product is non-soluble (in water).
Melting point/freezing point	: >300°C [EN ISO 3016]	
Initial boiling point and	: Not applicable.	
boiling range		
Flash point	: Not applicable.	
Flammability	: Yes.	



SDS # :

081734

Lower and upper explosion limit	:	Not applicable.
Vapor pressure	:	Not applicable.
Vapor density	:	Not applicable.
Relative density	:	0.9 [ASTM D 4052]
Density	:	0.9 g/cm³ [20°C] [ASTM D 4052]
Solubility(ies)	:	
Media		Result
water		Not soluble
Solubility in water	:	0.857 g/l
Miscible with water	:	No.
Partition coefficient: n-octanol/ water	:	>3.5
Auto-ignition temperature	:	Not applicable.
Decomposition temperature	:	>300°C
Beeenipeenien temperature		
Viscosity		Not applicable.

9.2 Other information

r

No other relevant physical and chemical parameters for the safe use of the product

SECTION 10: Stabilit	ty and reactivity
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
10.2 Chemical stability	: Stable under recommended storage and handling conditions (see Section 7).
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
10.4 Conditions to avoid	: No specific data.
10.5 Incompatible materials	: Strong oxidizing agents
10.6 Hazardous decomposition products	: carbon monoxide carbon dioxide nitrogen oxides sulfur oxides Hydrogen sulfide Mercaptans



SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
■ Penzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	LD50 Dermal	Rat - Male, Female	>2000 mg/kg	-	OECD 402 Read across
Benzenamine, N-phenyl-,	LD50 Oral LD50 Oral	Rat - Female Rat	4445 mg/kg >2500 mg/kg	-	-
reaction products with 2,4,4-trimethylpentene					

Acute toxicity estimates

Product/substance	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	4445	N/A	N/A	N/A	N/A

Conclusion/Summary : Based on available data, the classification criteria are not met.

.. .. 10

Product/substance	Resu	lt	Species	Score	Exposure	Test
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	Eyes - Irritant		Rabbit	1	-	OECD 405
, , , , , , , , , , , , , , , , , , ,	Skin - Erythema/E	Schar	Rabbit	2.7	4 hours	OECD 404
Conclusion/Summary					·	·
Skin	: Based on availa	able data, the	classification of	riteria are	not met.	
Eyes	: Based on availa	able data, the	classification of	riteria are	met.	
Respiratory	: Based on availa	able data, the	classification of	riteria are	not met.	
<u>Sensitization</u>						
Product/substance	Route of	s	pecies		Resu	ılt
	exposure					
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	skin	Guinea pig		Not s	ensitizing	
Conclusion/Summary		•		·		
Skin	: Based on availa	able data, the	classification of	riteria are	not met.	
Respiratory	: Based on availa	able data, the	classification of	riteria are	not met.	
<u>Mutagenicity</u>						
Conclusion/Summary	: Based on availa	able data, the	classification of	riteria are	not met.	
Carcinogenicity						
Conclusion/Summary	: Based on availa	able data, the	classification o	riteria are	not met.	
Reproductive toxicity						
Conclusion/Summary	: Based on availa	able data, the	classification of	riteria are	not met.	
<u>Teratogenicity</u>						
Conclusion/Summary	: Based on availa	able data, the	classification of	riteria are	not met.	
Specific target organ toxicity	<u>y (single exposure</u>	<u>e)</u>				
Conclusion/Summary	: Based on availa	able data, the	classification of	riteria are	not met.	
Specific target organ toxicity	v (repeated expos	ure)				

: Based on available data, the classification criteria are not met. Conclusion/Summary



Aspiration hazard		
Conclusion/Summary	:	Ba

Summary : Based on available data, the classification criteria are not met.

Information on the likely	: Not available.
routes of exposure	

Potential acute health effects

Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

<u>Short term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health effe	<u>icts</u>
Not available.	
Conclusion/Summary	: Not available.
General	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

Not available.



SECTION 12: Ecological information

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	Acute EC50 29 mg/l	Algae - Pseudokirchneriella subcapitata	96 hours	STDMETH, ASTM and USEPA 201
	Acute EC50 2.9 mg/l	Crustaceans - Daphnia magna	48 hours	OECD 202
	Acute LC50 1.67 mg/l	Fish - Lepomis macrochirus	96 hours	STDMETH, ASTM and USEPA
	Chronic NOEC 0.5 mg/l	Algae - Pseudokirchneriella subcapitata	96 hours	STDMETH, ASTM and USEPA 201
	Chronic NOEC 0.379 mg/l	Daphnia	48 hours	OECD 211

Conclusion/Summary

: Not available.

12.2 Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	OECD 301B	>90 % - Readily - 28 days	-	Activated sludge

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Penzenesulfonic acid, C10-13-alkyl derivs., Ca Salt Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	-	-	Readily Not readily

12.3 Bioaccumulative potential

Product/substance	LogKow	BCF	Potential
NEVASTANE XS 80	>3.5	-	Low
Benzenesulfonic acid, C10-13-alkyl derivs., Ca Salt	2.89	-	Low
Benzenamine, N-phenyl-, reaction products with 2,4,4-trimethylpentene	5.1	1730	High

Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Not available.
Mobility in soil	: Given its physical and chemical characteristics, the product has no soil mobility. The product is insoluble and floats on water Loss by evaporation is limited

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %.

12.6 Endocrine disrupting properties

Revision:2023/08/11	Version : 3	Germany	ENGLISH	11/35
---------------------	-------------	---------	---------	-------



This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACh Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Dispo	SECTION 13: Disposal considerations		
13.1 Waste treatment meth	nods		
Product			
Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.		
Hazardous waste	: Yes.		
	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used The following Waste Codes are only suggestions: 12 01 12*		
Packaging			
Methods of disposal	 The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. 		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.



14.7 Maritime transport in : Not available. **bulk according to IMO instruments**

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture <u>EU Regulation (EC) No. 1907/2006 (REACH)</u>

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

<u>Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous</u> <u>substances, mixtures and articles</u>

Other EU regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air Industrial emissions : Not listed (integrated pollution

prevention and control) -

Water

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

Storage class (TRGS 510) : 11

Hazardous incident ordinance

This product is not controlled under the Germany Hazardous Incident Ordinance.

Hazard class for water	: 2
Technical instruction on air quality control	:
Employment law	: Law on the protection of young workers Regulation on the complementary implementation of the EC Directive on Maternity Protection (MuSchRiV - Maternity Protection Directive Regulation)



International	regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals	
Not listed.	

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants Not listed.

Rotterdam Convention on Prior Informed Consent (PIC) Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals Not listed.

LU - Luxembourg prohibited chemicals in the workplace Not listed.

Inventory list

<u></u>	
Australia inventory (AIIC)	: All components are listed or exempted.
Canada inventory (DSL/NDSL)	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory (EC)	: All components are listed or exempted.
Japan inventory	 Japan inventory (CSCL): All components are listed or exempted. Japan inventory (ISHL): All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC)	: All components are listed or exempted.
Philippines inventory (PICCS)	: All components are listed or exempted.
Korea inventory (KECI)	: All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	: 🕅 components are listed or exempted.
Thailand inventory	: Not determined.
Turkey inventory	: At least one component is not listed.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: All components are listed or exempted.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical Safety: See exposure scenarios**Assessment**



SECTION 16: Other information

Indicates information that has changed from previously issued version.	
Abbreviations and acronyms: ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Pack 1272/2008] DNEL = Derived No Effect Level DMEL = Derived Minimal Effect Level EUH statement = CLP-specific Hazard s N/A = Not available PBT = Persistent, Bioaccumulative and T vPvB = Very Persistent and Very Bioaccu PNEC = Predicted No Effect Concentrati LC50 = Median lethal concentration LD50 = Median lethal dose OEL = Occupational Exposure Limit VOC = Volatile Organic Compound	tatement Toxic umulative ion e composition, Complex reaction products
QSAR = Quantitative Structure–Activity F	Relationship

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification		Justification
Eye Irrit. 2, H319		Calculation method
Full text of abbreviated H statements		·
▶315Causes skin irritationH318Causes serious eyeH319Causes serious eyeH361fSuspected of damageH412Harmful to aquatic lit		damage. irritation.
Full text of classifications [CLP/GHS]		
Aquatic Chronic 3 Eye Dam. 1 Eye Irrit. 2 Repr. 2 Skin Irrit. 2	SERIOUS EYE DAN SERIOUS EYE DAN TOXIC TO REPROI	(LONG-TERM) - Category 3 MAGE/ EYE IRRITATION - Category 1 MAGE/ EYE IRRITATION - Category 2 DUCTION - Category 2 /IRRITATION - Category 2

Date of revision	: 2023/08/11
previous revision date	: 2022/09/20
Version	: 3
Notice to reader	



To the best of our knowledge, the information contained herein is accurate. However, neither the abovenamed supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Identification of the substance or mixture

Professional

Product definition	: Mixture
Code	: 081734
Product name	: NEVASTANE XS 80
Section 1 - Title	
Short title of the exposure scenario	: Use of lubricants and greases in open systems - Professional
List of use descriptors	 Identified use name: Use of lubricants and greases in open systems - Professional Process Category: PROC01, PROC02, PROC08a, PROC10, PROC11, PROC13 Sector of end use: SU22 Subsequent service life relevant for that use: No. Environmental Release Category: ERC08a, ERC08d
Health Contributing scenarios	: General measures applicable to all activities Material transfers Manual - PROC08a Roller, spreader, flow application - PROC10 Spraying - PROC11 Treatment of articles by dipping and pouring - PROC13 Equipment cleaning and maintenance - PROC08a Storage - PROC01, PROC02
Processes and activities covered by the exposure scenario	: Covers use of lubricants and greases in open systems, including application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mold releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.

Section 2 - Exposure controls

Contributing scenario contro No exposure scenario require		ng environmental exposure for 1:
Contributing scenario contro	ollir	ng worker exposure for 2: General measures applicable to all activities
Concentration of substance in mixture or article	-	Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	:	Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	:	Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	-	Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures re	late	ed to personal protection, hygiene and health evaluation
Advice on general occupational hygiene	:	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	:	Use suitable eye protection.

NEVASTANE XS 80	- Use of lubricants and greases in open systems Professional
Contributing scenario contro	olling worker exposure for 3: Material transfers Manual
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
Contributing scenario contro	olling worker exposure for 4: Roller, spreader, flow application
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario contro	olling worker exposure for 5: Spraying
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear suitable coveralls to prevent exposure to the skin. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Respiratory protection	: Wear a respirator conforming to EN140 with type A/P2 filter or better.
Contributing scenario contro	olling worker exposure for 6: Treatment of articles by dipping and pouring
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Contributing scenario contro	olling worker exposure for 7: Equipment cleaning and maintenance
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Technical conditions and measures at process level (source) to prevent release	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (5 to 15 air changes per hour) Natural ventilation is from doors, windows etc. Controlled ventilation means air is supplied or removed by a powered fan.
Contributing scenario contro	olling worker exposure for 8: Storage
Engineering controls	: Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website:	:	Not applicable.	
Exposure estimation and ref	fere	nce to its source - Environment: 1:	
Exposure assessment (environment):	:	Used ECETOC TRA model.	
Exposure estimation and reference to its source	:	Not available.	
Exposure estimation and ref	fere	nce to its source - Workers: 2: General measures applicable to all activitie	S
Exposure assessment (human):	:	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.	
Exposure estimation and reference to its source	:	Not available.	
Date of issue/Date of revisio	n	: 7/8/2020	18/35

NEVASTANE XS 80	- Use of lubricants and greases in open systems Professional
Exposure estimation and ref	erence to its source - Workers: 3: Material transfers Manual
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 4: Roller, spreader, flow application
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 5: Spraying
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 6: Treatment of articles by dipping and pouring
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 7: Equipment cleaning and maintenance
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	erence to its source - Workers: 8: Storage
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Identification of the substance or mixture **Product definition** : Mixture : 081734 Code : NEVASTANE XS 80 **Product name** Section 1 - Title Short title of the exposure : Formulation additives, lubricants and greases - Industrial scenario List of use descriptors : Identified use name: Formulation additives, lubricants and greases - Industrial Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15 Sector of end use: SU03, SU10 Subsequent service life relevant for that use: No. Environmental Release Category: ERC02 **Health Contributing** : General measures applicable to all activities scenarios General exposures Use in contained systems Elevated temperature - PROC02 Mixing operations Closed systems Batch processes at elevated temperatures -PROC03 Mixing operations Open systems Batch processes at elevated temperatures -PROC04, PROC05 Mixing operations (open systems) - PROC04, PROC05 Process sampling - PROC04, PROC08b Bulk transfers Dedicated facility - PROC08b Drum/batch transfers Dedicated facility - PROC08b Drum/batch transfers Non-dedicated facility - PROC08a Equipment cleaning and maintenance - PROC08a, PROC08b Drum and small package filling - PROC09 Laboratory activities - PROC15 Storage - PROC01, PROC02 **Processes and activities** : Industrial formulation of lubricant additives, lubricants and greases. Includes material transfers, mixing, large and small scale packing, sampling, maintenance. covered by the exposure scenario

Section 2 - Exposure controls

Contributing scenario contro	olling worker exposure for 2: General measures applicable to all activities
Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100 %. (unless stated differently)
Physical state	: Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure
Amounts used	: Not applicable.
Frequency and duration of use/exposure	: Covers daily exposures up to 8 hours (unless stated differently)
Human factors not influenced by risk management	: Not applicable.
Other conditions affecting workers exposure	: Covers percentage substance in the product up to 100% (unless stated differently)
Conditions and measures re	lated to personal protection, hygiene and health evaluation

Industrial

NEVASTANE XS 80	- Formulation additives, lubricants and greases Industrial
Advice on general occupational hygiene	: Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	: Use suitable eye protection.
Contributing scenario contro Elevated temperature	olling worker exposure for 3: General exposures Use in contained systems
No other specific measures in	dentified.
Contributing scenario contro at elevated temperatures	olling worker exposure for 4: Mixing operations Closed systems Batch processes
Ventilation control measures	: Provide extract ventilation to points where emissions occur.
Contributing scenario contro elevated temperatures	olling worker exposure for 5: Mixing operations Open systems Batch processes at
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Ventilation control measures	: Provide extract ventilation to points where emissions occur.
Contributing scenario contro	olling worker exposure for 6: Mixing operations (open systems)
Ventilation control measures	: Provide extract ventilation to points where emissions occur.
-	olling worker exposure for 7: Process sampling
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
	elated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
-	olling worker exposure for 8: Bulk transfers Dedicated facility
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
	elated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Contributing scenario contre	olling worker exposure for 9: Drum/batch transfers Dedicated facility
Ventilation control measures	: Provide extract ventilation to points where emissions occur.
Contributing scenario contro	olling worker exposure for 10: Drum/batch transfers Non-dedicated facility
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
Ventilation control measures	: Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).
Conditions and measures re	elated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.

NEVASTANE XS 80	- Formulation additives, lubricants and greases Industrial
Contributing scenario cont	rolling worker exposure for 11: Equipment cleaning and maintenance
Technical conditions and measures to control dispersion from source towards the worker	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down and flush system prior to equipment break-in or maintenance.
Conditions and measures r	elated to personal protection, hygiene and health evaluation
Advice on general occupational hygiene	: Clear spills immediately.
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Contributing scenario cont	rolling worker exposure for 12: Drum and small package filling
Ventilation control measures	 Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).
Conditions and measures r	elated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario cont	rolling worker exposure for 13: Laboratory activities
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Contributing scenario cont	rolling worker exposure for 14: Storage
Engineering controls	: Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.
Exposure estimation and ref	rence to its source - Environment: 1:
Exposure assessment (environment):	: Used ECETOC TRA model.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	rence to its source - Workers: 2: General measures applicable to all activities
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref Elevated temperature	rence to its source - Workers: 3: General exposures Use in contained systems
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref processes at elevated tempe	rence to its source - Workers: 4: Mixing operations Closed systems Batch ratures
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

NEVASTANE XS 80	Formulation additives, lubricants and greases Industria		
Exposure estimation and ref processes at elevated tempe	ference to its source - Workers: 5: Mixing operations Open systems Batch eratures		
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product. 		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref	ference to its source - Workers: 6: Mixing operations (open systems)		
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product. 		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref	ference to its source - Workers: 7: Process sampling		
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product. 		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref	ference to its source - Workers: 8: Bulk transfers Dedicated facility		
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref	ference to its source - Workers: 9: Drum/batch transfers Dedicated facility		
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ret	ference to its source - Workers: 10: Drum/batch transfers Non-dedicated facility		
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref	ference to its source - Workers: 11: Equipment cleaning and maintenance		
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and re	ference to its source - Workers: 12: Drum and small package filling		
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product. 		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and re	ference to its source - Workers: 13: Laboratory activities		
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		

NEVASTANE XS 80	- Formulation additives, lubricants and greases Industrial
Exposure estimation and ref	erence to its source - Workers: 14: Storage
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e.,
Health	 RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction. Where other risk management measures/operational conditions are adopted, then
	users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Product definition : Mixture : 081734 Code : NEVASTANE XS 80 **Product name** Section 1 - Title Short title of the exposure : General use of lubricants and greases in vehicles or machinery - Industrial scenario List of use descriptors : Identified use name: General use of lubricants and greases in vehicles or machinery - Industrial Process Category: PROC01, PROC02, PROC08b, PROC09 Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC04, ERC07 **Health Contributing** : General measures applicable to all activities scenarios General exposures (closed systems) - PROC01 Initial factory fill of equipment Use in contained systems - PROC02, PROC09 Initial factory fill of equipment Open systems - PROC08b Operation of equipment containing engine oils and similar Use in contained systems - PROC01 Equipment cleaning and maintenance - PROC08b Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature) - PROC08b Storage - PROC01, PROC02 Covers general use of lubricants and greases in vehiculs or machinery in closed **Processes and activities** ÷ covered by the exposure systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities. scenario

Section 2 - Exposure controls

Contributing scenario contro No exposure scenario require		ng environmental exposure for 1:
Contributing scenario contro	ollir	ng worker exposure for 2: General measures applicable to all activities
Concentration of substance in mixture or article	:	Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	:	Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	1	Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	-	Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures rel	ate	ed to personal protection, hygiene and health evaluation
Advice on general occupational hygiene	:	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	:	Use suitable eye protection.

Identification of the substance or mixture

NEVASTANE XS 80	General use of lubricants and greases in vehicles or machinery - Industrial
Contributing scenario contro No other specific measures in	Iling worker exposure for 3: General exposures (closed systems) Ientified.
Contributing scenario contro systems No other specific measures io	elling worker exposure for 4: Initial factory fill of equipment Use in contained
Contributing scenario contro Frequency and duration of use/exposure Ventilation control	 Avoid carrying out activities involving exposure for more than 4 hours per day. Provide a good standard of general or controlled ventilation (10 to 15 air changes
measures	per hour)
Contributing scenario contro similar Use in contained sys No other specific measures in	
Contributing scenario contro	Iling worker exposure for 7: Equipment cleaning and maintenance
Technical conditions and measures at process level (source) to prevent release	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls Ventilation control measures	 Drain down system prior to equipment break-in or maintenance. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
	olling worker exposure for 8: Equipment cleaning and maintenance Operation is erature (> 20°C above ambient temperature)
Technical conditions and measures to control dispersion from source towards the worker	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.
Ventilation control measures	: Provide extract ventilation to emission points when contact with warm (>50°C) lubricant is likely.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Contributing scenario contro	olling worker exposure for 9: Storage
Engineering controls	: Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.
Exposure estimation and ref	rence to its source - Environment: 1:
Exposure assessment (environment):	: Used ECETOC TRA model.
Exposure estimation and reference to its source	: Not available.

NEVASTANE XS 80	General use of lubricants and greases in vehicles or machinery - Industrial
Exposure estimation and ref	ference to its source - Workers: 2: General measures applicable to all activities
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 3: General exposures (closed systems)
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 4: Initial factory fill of equipment Use in contained
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 5: Initial factory fill of equipment Open systems
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref and similar Use in contained	ference to its source - Workers: 6: Operation of equipment containing engine oils I systems
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and ref	ference to its source - Workers: 7: Equipment cleaning and maintenance
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
	ference to its source - Workers: 8: Equipment cleaning and maintenance Operation nperature (> 20°C above ambient temperature)
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.
Exposure estimation and re	ference to its source - Workers: 9: Storage
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

NEVASTANE XS 80	General use of lubricants and greases in vehicles or machinery - Industrial
Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the sub	Identification of the substance or mixture	
Product definition	: Mixture	
Code	: 081734	
Product name	: NEVASTANE XS 80	
Section 1 - Title		
Short title of the exposure scenario	: General use of lubricants and greases in vehicles or machinery - Professional	
List of use descriptors	 Identified use name: General use of lubricants and greases in vehicles or machinery - Professional Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20 Sector of end use: SU22 Subsequent service life relevant for that use: No. Environmental Release Category: ERC09a, ERC09b 	
Health Contributing scenarios	 General measures applicable to all activities Operation of equipment containing engine oils and similar Use in contained systems - PROC01 Material transfers Non-dedicated facility - PROC08a Equipment cleaning and maintenance Dedicated facility - PROC08b, PROC20 Storage - PROC01, PROC02 	
Processes and activities covered by the exposure scenario	: Covers general use of lubricants and greases in vehiculs or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.	

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1: No exposure scenario required	
Contributing scenario contro	olling worker exposure for 2: General measures applicable to all activities
Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	: Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	: Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	 Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Advice on general occupational hygiene	: Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	: Use suitable eye protection.

similar Use in contained systems

No other specific measures identified.

NEVASTANE XS 80	General use of lubricants and greases in vehicles or machinery - Professional
Contributing scenario contro	Iling worker exposure for 4: Material transfers Non-dedicated facility
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 4 hours per day.
Conditions and measures re	ated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario contro facility	Iling worker exposure for 5: Equipment cleaning and maintenance Dedicated
Technical conditions and measures at process level (source) to prevent release	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.
Contributing scenario contro	Iling worker exposure for 6: Storage
Engineering controls	: Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website:	: Not applicable.		
Exposure estimation and ref	erence to its source - Environment: 1:		
Exposure assessment (environment):	: Used ECETOC TRA model.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref	erence to its source - Workers: 2: General measures applicable to all activities		
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and reference to its source - Workers: 3: Operation of equipment containing engine oils and similar Use in contained systems			
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref	erence to its source - Workers: 4: Material transfers Non-dedicated facility		
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		
Exposure estimation and ref facility	Exposure estimation and reference to its source - Workers: 5: Equipment cleaning and maintenance Dedicated facility		
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.		
Exposure estimation and reference to its source	: Not available.		

NEVASTANE XS 80	General use of lubricants and greases in vehicles or machinery - Professional
Exposure estimation and ref	ference to its source - Workers: 6: Storage
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Product definition : Mixture : 081734 Code : NEVASTANE XS 80 **Product name** Section 1 - Title Short title of the exposure : Use of lubricants and greases in open systems - Industrial scenario List of use descriptors : Identified use name: Use of lubricants and greases in open systems - Industrial Process Category: PROC01, PROC02, PROC07, PROC08b, PROC09, PROC10, PROC13 Sector of end use: SU03 Subsequent service life relevant for that use: No. Environmental Release Category: ERC04 **Health Contributing** : General measures applicable to all activities scenarios Material transfers Manual - PROC08b Material transfers Automated process with (semi) closed systems - PROC08b, PROC09 Roller, spreader, flow application - PROC10 Spraying - PROC07 Treatment of articles by dipping and pouring - PROC13 Equipment cleaning and maintenance - PROC08b Storage - PROC01, PROC02 **Processes and activities** Covers use of lubricants and greases in open systems, including application of 2 lubricant to work pieces or equipment by dipping, brushing or spraying (without covered by the exposure exposure to heat), e.g. mold releases, corrosion protection, slideways. Includes scenario associated product storage, material transfers, sampling and maintenance activities

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1: No exposure scenario required		
Contributing scenario contro	llii	ng worker exposure for 2: General measures applicable to all activities
Concentration of substance in mixture or article	:	Covers percentage substance in the product up to 100% (unless stated differently).
Physical state	:	Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure.
Frequency and duration of use/exposure	:	Covers daily exposures up to 8 hours (unless stated differently).
Other conditions affecting workers exposure	:	Assumes use at not more than 20°C above ambient temperature. unless stated differently. Assumes a good basic standard of occupational hygiene has been implemented.
Conditions and measures rel	ate	ed to personal protection, hygiene and health evaluation
Advice on general occupational hygiene	:	Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Other skin protection measures such as impervious suits and face shields may be required during high dispersion activities which are likely to lead to substantial aerosol release, e.g. spraying. Avoid direct eye contact with product, also via contamination on hands.
Personal protection	1	Use suitable eye protection.

Identification of the substance or mixture

NEVASTANE XS 80	- Use of lubricants and greases in open systems Industrial
Contributing scenario contro	olling worker exposure for 3: Material transfers Manual
Frequency and duration of use/exposure	: Avoid carrying out activities involving exposure for more than 1 hour per day.
Contributing scenario contro closed systems	olling worker exposure for 4: Material transfers Automated process with (semi)
Ventilation control measures	: Ensure material transfers are under containment or extract ventilation.
Contributing scenario contro	olling worker exposure for 5: Roller, spreader, flow application
Ventilation control measures	: Provide extract ventilation to points where emissions occur.
Contributing scenario contro	olling worker exposure for 6: Spraying
Ventilation control measures	: Carry out in a vented booth or extracted enclosure.
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario contro	olling worker exposure for 7: Treatment of articles by dipping and pouring
Ventilation control measures	 Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour)
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with intensive management supervision controls.
Contributing scenario contro	olling worker exposure for 8: Equipment cleaning and maintenance
Technical conditions and measures at process level (source) to prevent release	: Retain drain-downs in sealed storage pending disposal or for subsequent recycle.
Engineering controls	: Drain down system prior to equipment break-in or maintenance.
Ventilation control measures	: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).
Conditions and measures re	lated to personal protection, hygiene and health evaluation
Personal protection	: Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.
Contributing scenario contro	olling worker exposure for 9: Storage
Engineering controls	: Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website:	ot applicable.			
Exposure estimation and reference to its source - Environment: 1:				
Exposure assessment (environment):	sed ECETOC TRA model.			
Exposure estimation and reference to its source	ot available.			
Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities				
Exposure assessment (human):	he risk Management Mesures/Operational Conditions that are ide xposure Scenario are the outcome of a quantitative and qualitativ at covers this product.			
Exposure estimation and reference to its source	ot available.			

NEVASTANE XS 80	- Use of lubricants and greases in open systems Industrial			
Exposure estimation and reference to its source - Workers: 3: Material transfers Manual				
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.			
Exposure estimation and reference to its source	: Not available.			
Exposure estimation and ref (semi) closed systems	erence to its source - Workers: 4: Material transfers Automated process with			
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.			
Exposure estimation and reference to its source	: Not available.			
Exposure estimation and ref	erence to its source - Workers: 5: Roller, spreader, flow application			
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.			
Exposure estimation and reference to its source	: Not available.			
Exposure estimation and ref	erence to its source - Workers: 6: Spraying			
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.			
Exposure estimation and reference to its source	: Not available.			
Exposure estimation and ref	erence to its source - Workers: 7: Treatment of articles by dipping and pouring			
Exposure assessment (human):	 The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product. 			
Exposure estimation and reference to its source	: Not available.			
Exposure estimation and reference to its source - Workers: 8: Equipment cleaning and maintenance				
Exposure assessment (human):	The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.			
Exposure estimation and reference to its source	: Not available.			
Exposure estimation and reference to its source - Workers: 9: Storage				
Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.			
Exposure estimation and reference to its source	: Not available.			

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction.
Health	 Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction.

NEVASTANE XS 80		- Use of lubricants and greases in open systems Industrial		
Additional good practice advice beyond the REACH CSA				
Environment	: Not available.			
Health	: Not available.			