

LINE CARD | perma LUBRICANTS



For more than 50 years, perma has stood for innovative and creative lubrication solutions. Now, we are extending our exclusive line of perma greases to enhance our product offerings and ensure an uninterrupted supply chain. With our many years of experience, we can offer you a wide range of high-quality lubricants designed to meet your needs. Our comprehensive family of greases have been specifically developed to meet the rigorous heavy industry demands of our customers while providing superior protection for critical rotating equipment such as conveyors, pumps, fans, and electric motors. The perma range includes multipurpose, food, speed and heavy load greases with petroleum or synthetic base.

perma Grease name	Grease Specification						Grease Applications				Grease Characteristics					
	Thickener type	Oil type	cSt @ 40°C	NLGI	Temperature Range	Color	Electric Motors	Fans & Blowers	Pumps	Conveyors	High Speed	Low Speed	High Load	Mod Load / EP	Low Load	Water
perma SPEED LX 100-2 (SF140)	Lithium Complex	Mineral	115	2	-20°C - 150°C -4°F - 302°F	Brown	**	*	*	-	***	*	-	-	***	*
perma SPEED PU 100-2 (SF141)	Polyurea	Mineral	128	2	-23°C - 198°C -10°F - 390°F	Blue	***	*	*	-	***	*	-	-	***	**
perma SPEED LX SYN 100-2 (SF152)	Lithium Complex	Synthetic	100	2	-40°C - 149°C -40°F - 300°F	White	**	***	***	-	***	*	-	*	***	**
perma MULTI LC 150-2 (SF01)	Lithium Calcium	Mineral	150	2	-30°C - 130°C -22°F - 266°F	Brown	*	**	**	**	*	***	**	**	*	***
perma MULTI LX 220-1 (SF101)	Lithium Complex	Mineral	220	1	-18°C - 140°C 0°F - 284°F	Blue/Green	*	**	**	***	*	***	**	**	*	**
perma MULTI LX 220-2 (SF111)	Lithium Complex	Mineral	220	2	-18°C - 140°C 0°F - 284°F	Blue/Green	*	**	**	***	*	***	**	**	*	**
perma MULTI LC SYN 220-1 (SF120)	Lithium Calcium	Semi-Synthetic	230	1	-30°C - 140°C -22°F - 284°F	Blue	*	***	***	**	*	***	**	**	*	**
perma MULTI LC SYN 220-2 (SF130)	Lithium Calcium	Semi-Synthetic	230	2	-30°C - 140°C -22°F - 284°F	Blue	*	***	***	**	*	***	**	**	*	**
perma LOAD LX 460-1 (SF181)	Lithium Complex	Mineral	460	1	-18°C - 140°C 0°F - 284°F	Amber	-	-	-	***	-	***	***	***	-	***
perma LOAD LX 460-2 (SF191)	Lithium Complex	Mineral	460	2	-18°C - 140°C 0°F - 284°F	Amber	-	-	-	***	-	***	***	***	-	***
perma FOOD AX SYN 150-1 (SF10)	Aluminium Complex	Synthetic	150	1	-45°C - 120°C -49°F - 248°F	Beige	-	**	**	**	*	**	**	**	*	***
perma FOOD CS SYN 220-1 (SF161)	Calcium Sulphonate	Synthetic	220	1	-40°C - 190°C -40°F - 375°F	Off White	-	**	**	**	*	**	**	**	*	***
perma FOOD CS SYN 220-2 (SF171)	Calcium Sulphonate	Synthetic	220	2	-40°C - 190°C -40°F - 375°F	Off White	-	**	**	**	*	**	**	**	*	***

Not Recommended: - | Ok: * | Good: ** | Excellent: ***